

**ARDLEIGH SAILING CLUB
RESCUE BOAT PROCEDURE
RIGIFLEX DINGHY**

**AT LEAST ONE CREW MEMBER SHOULD BE PREPARED TO ENTER
THE WATER IF NECESSARY**

**FOR MORE DETAIL INSTRUCTIONS REFER TO PICTORIAL
SAFETY BOAT INSTRUCTIONS IN THE START HUT**

LAUNCH PROCEDURE

- 1 Obtain radios and (Rigifix) key from the male changing room locker.**
- 2 Carry out radio check with start hut.**
- 3 Obtain the keys to the container from the OOD
Open container and place ramp in position.**
- 4 Turn on battery isolator switch and raise the engine.**
- 5 Push boat from the container (2 people).**
- 6 Obtain fuel tank from the fuel store.
Check contents - should be at least half full.**
- 7 Instal the fuel tank in the boat.**
- 8 Insert drainage bungs.**
- 9 Launch boat (2 people) and moor to the pontoon.**
- 10 Lower the engine.**
- 11 Prime fuel into the engine, ensure kill cord is in position,
Gear in neutral.
Throttle in "Start" position.
Start the engine by turning the ignition key.**
- 12 Check flow of cooling water.**
- 13 Trial boat on the water.
Advise OOD that boat is operational.**

ARDLEIGH SAILING CLUB
RESCUE BOAT PROCEDURE
RIGIFLEX DINGHY

**FOR MORE DETAIL INSTRUCTIONS REFER TO PICTORIAL
SAFETY BOAT INSTRUCTIONS IN THE START HUT**

RECOVERY PROCEDURE

- 1 Switch off ignition and raise the engine.**
- 2 Position the trolley in the water, manually tow the boat into the cradle and tie the mooring line to the trailer.**
- 3 Pull the trailer up to the level standing (3 people + winch).**
- 4 Remove the fuel tank and return it to the fuel store.
Lock the door of the fuel store.**
- 5 Push the trailer into the container.**
- 6 Lower the engine to touch the floor.**
- 7 Turn off the battery isolator switch and remove the ignition key.**
- 8 Close and lock the container doors.
Return the main bunch of keys to the OOD.**
- 9 Return the radios and the ignition key to the locker in the male changing room.
Put the radios on charge.**